

BTA Towbars

Australia's Towing Equipment Specialist



Fitting Instructions: TOY046 & 52

| | |
|-------------------------|---|
| Vehicle: | Toyota Yaris 3/5 Door Hatch (2006 On) |
| Towing Capacity: | 500kg |
| Fitting Kit: | 1x 1½ x ⅜ bolt, nut, spring & flat washer |
| | 1x large round plate |
| | 1x 'D' shackle |
| | 2x Towbar Rating Labels |

| | |
|-----|---|
| 1. | Remove spare wheel. |
| 2. | Remove rubber grommet from spare wheel floor. |
| 3. | Remove rear tail lights. |
| 4. | Remove rear bumper bar. |
| 5. | Remove & discard rear crash support panel. |
| 6. | Fit towbar using original bolts to existing holes in rear panel, tighten. |
| 7. | Fit 1½ x ⅜ bolt with plate supplied hole in spare wheel which aligns with towbar base plate (if two holes present - use hole furthest from towball mount), fit nut complete with spring washer – tighten. |
| 8. | Check all bolts for tightness. |
| 9. | Refit bumper bar, tail lights & spare wheel. |
| 10. | Apply Towbar Rating Labels to driver's side door sill <u>and</u> non-removable part of the towbar. |